## **Product information sheet** Supplier's name or trade mark: Paulmann Licht GmbH Supplier's address Quezinger Feld 2, DE-31832 Springe-Völksen Model identifier: Type of light source: other than listed other than listed Non-directional or directional: **NDLS** Lighting technology used: Light source cap-type (or other electric E27 interface) MLS Connected light source (CLS): Mains or non-mains: no Colour-tuneable light source: Envelope: no no cover High luminance light source: no Anti-glare shield: Dimmable: mit bestimmten no Dimmern Product parameters **Parameter** Value **Parameter** Value General product parameters: 7 Energy consumption in on-mode (kWh/1 G Energy efficiency class: 000 h), rounded up to the nearest integer Useful luminous flux (Фuse), indicating 390 at 360 ° 2000 Correlated colour temperature, rounded if it refers to the flux in a sphere (360°), to the nearest 100 K, or the range of in a wide cone (120°) or in a narrow correlated colour temperatures, cone (90°) rounded to the nearest 100 K, that can be set: On-mode power (Pon), expressed in W 7 Standby power (Psb), expressed in W and rounded to the second decimal Networked standby power (Pnet) for Colour rendering index, rounded to the CLS, expressed in W and rounded to the nearest integer, or the range of CRIsecond decimal values that can be set **Outer dimensions** Height 315 Spectral power distribution in the range without separate 250 nm to 800 nm, at full-load control gear, Width 160 lighting control parts and non-Depth 160 . lighting control parts, if any (millimetre) Claim of equivalent power yes If yes, equivalent power (W) 35 W Chromaticity coordinates (x and y) Parameters for directional light sources: Peak luminous intensity (cd) Beam angle in degrees, or the range of beam angles that can be set Parameters for LED and OLED light sources: Survival factor R9 colour rendering index value The lumen maintenance factor 75 Parameters for LED and OLED mains light sources: Displacement factor (cos φ1) 0.8 Colour consistency in McAdam ellipses 6 Claims that an LED light source no If yes, then replacement claim (W) replaces a fluorescent light source without integrated ballast of a p articular wattage. Flicker metric (Pst LM) Stroboscopic effect metric (SVM)