

Product information sheet



Supplier's name or trade mark:		Paulmann Licht GmbH		
Supplier's address		Quezinger Feld 2, DE-31832 Springe-Völksen		
Model identifier:		29172		
Type of light source:		LED		
Lighting technology used:	LED	Non-directional or directional:	NDLS	
Light source cap-type (or other electric interface)	G13			
Mains or non-mains:	NMLS	Connected light source (CLS):	no	
Colour-tuneable light source:	no	Envelope:	no cover	
High luminance light source:	no			
Anti-glare shield:	no	Dimmable:	nein	
Product parameters				
Parameter		Value	Parameter	
			Value	
General product parameters:				
Energy consumption in on-mode (kWh/1 000 h), rounded up to the nearest integer		11	Energy efficiency class:	
			F	
Useful luminous flux (Φ _{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		1150 at 360 °	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set:	
			3000	
On-mode power (P _{on}), expressed in W		11	Standby power (P _{sb}), expressed in W and rounded to the second decimal	
			80	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal			Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	Height	604	Spectral power distribution in the range 250 nm to 800 nm, at full-load	
	Width	27		
	Depth	27		
Claim of equivalent power		yes	If yes, equivalent power (W)	
			80 W	
		Chromaticity coordinates (x and y)	0,442	
			0,404	
Parameters for directional light sources:				
Peak luminous intensity (cd)			Beam angle in degrees, or the range of beam angles that can be set	
Parameters for LED and OLED light sources:				
R9 colour rendering index value		4	Survival factor	
			100	
The lumen maintenance factor		98		
Parameters for LED and OLED mains light sources:				
Displacement factor (cos φ ₁)		0,84	Colour consistency in McAdam ellipses	
			6	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		no	If yes, then replacement claim (W)	
Flicker metric (P _{st} LM)		0,1	Stroboscopic effect metric (SVM)	
			0,1	