## Product information sheet



| Product ir   | nformation  | sheet                           |   | Ρ        |
|--|---|---------------------------------|---|----------|
| Supplier's name or trade mark:   |   |                                 | Paulmann Licht GmbH   |          |
| Supplier's address   |   |                                 | Quezinger Feld 2, DE-31832 Springe-Völksen  |          |
| Model identifier:  |   |                                 | 29204<br>LED  |          |
| Type of light source:  |   |                                 |   |          |
| Lighting technology used:  |   | LED                             | Non-directional or directional:   | NDLS     |
| Light source cap-type (or other electric interface)  |   | E14                             |   |          |
| Mains or non-mains:  |   | MLS                             | Connected light source (CLS):   | no       |
| Colour-tuneable light source:  |   | no                              | Envelope:   | no cover |
| High luminance light source:   |   | no                              |   |          |
| Anti-glare shield:   |   | no                              | Dimmable:   | nein     |
| Product parameters   |   |                                 |   |          |
| Parameter  |   | Value                           | Parameter   | Value    |
|  |   | Genera                          | I product parameters:   |          |
| Energy consumption in on-mode (kWh/1<br>000 h), rounded up to the nearest<br>integer   |   | 4                               | Energy efficiency class:  | A        |
| Useful luminous flux (Фuse), indicating<br>if it refers to the flux in a sphere (360°),<br>in a wide cone (120°) or in a narrow<br>cone (90°)    |   | 840 at 360 °                    | Correlated colour temperature, rounded<br>to the nearest 100 K, or the range of<br>correlated colour temperatures,<br>rounded to the nearest 100 K, that can<br>be set: | 4000     |
| On-mode power (Pon), expressed in W  |   | 4                               | Standby power (Psb), expressed in W and rounded to the second decimal   |          |
| Networked standby power (Pnet) for<br>CLS, expressed in W and rounded to the<br>second decimal   |   |                                 | Colour rendering index, rounded to the<br>nearest integer, or the range of CRI-<br>values that can be set   | 80       |
| Outer dimensions<br>without separate<br>control gear,<br>lighting control<br>parts and non-<br>lighting control<br>parts, if any<br>(millimetre) | Height  | 78                              | Spectral power distribution in the range 250 nm to 800 nm, at full-load   |          |
|  | Width   | 45                              | ,,  |          |
|  | Depth   | 45                              |   |          |
| Claim of equivalent power  |   | yes                             | If yes, equivalent power (W)  | 62 W     |
|  |   | Chromaticity coordinates (x and | 0,38  |          |
|  |   | у)                              | 0,38  |          |
|  |   | Parameters f                    | or directional light sources:   |          |
| Peak luminous intensity (cd)   |   |                                 | Beam angle in degrees, or the range of beam angles that can be set  |          |
|  |   | Parameters for                  | LED and OLED light sources:   |          |
| R9 colour rendering index value  |   | 18                              | Survival factor   | 91       |
| The lumen maintenance factor   |   | 98                              |   |          |
|  |   | Parameters for LE               | D and OLED mains light sources:   |          |
| Displacement factor (cos φ1)   |   | 0,5                             | Colour consistency in McAdam ellipses   | 6        |
| Displacement factor  | Claims that an LED light source<br>replaces a fluorescent light source<br>without integrated ballast of a p articular<br>wattage. |                                 |   |          |
| Claims that an LED<br>replaces a fluoresce<br>without integrated b   | ent light source  | no                              | If yes, then replacement claim (W)  |          |