



Paulmann Licht GmbH  
Quezinger Feld 2  
31832 Springe  
Germany  
www.paulmann.com

Art.-Nr.: 795.44  
795.45

PPN 12/23

CE UK CA

1x [LED strip]

1x [RGBW Controller]

1x [Li-Ion Battery]

1x [Scissors]

**A**

795.44 Driver: 24VA  
795.45 Driver: 36VA

795.44: 1,5m  
795.45: 3m

167mm

off

**B**

Installation diagrams showing correct and incorrect mounting methods for different beam angles (a ≥ 60° and a < 60°) and radii (r > 30mm and r < 30mm). Includes symbols for correct (checkmark) and incorrect (cross) methods.

**C**

5m 120° 5m < 7m

Li-Ion

only use CR2025  
1x Li-Ion Battery (3V 150mAH)

Installation steps 1-5 for battery insertion into the controller.

**D**

IP20 IP44

Driver 24VA: incl. 1,5m, expandable not incl. max. 1,5m

Driver 36VA: 3m, max. 2m

Water Protection Art.-Nr.: 702.47

**E**

RGBW Controller

R.G.B.W .....

on

**F**

RGBW Controller

**G**

tunable white

Daylight: W

Neutralwhite: W + WW 25%, 50%, 75%...

Warmwhite: 25% / 50% / 75%... (W off)

RGBW Controller

**H**

RGBW Controller

FLASH

**I**

RGBW Controller

AUTO

**J**

RGBW Controller

QUICK

SLOW

**K**

RGBW Controller

JUMP3

**L**

RGBW Controller

JUMP7

**M**

RGBW Controller

FADE3

**N**

RGBW Controller

FADE7

